

		bar	psi	kg	lbs	mm	inch	mm	inch	mm	mm						
18"	Black Sidewall																
	17"	225/40 R18 RF	92 W	8.0	3.5	51	630	1389	230	9.1	632	35.1	8.3	10.5	299	1943	7.5 - 8.0
		225/45 R18	95 H	7.0	3.5	51	775	1709	245	9.6	690	27.1	8.3	10.5	319	2105	6.0 - 7.5
		225/45 R17	94 W	8.0	3.5	51	670	1477	235	9.3	644	25.4	8.3	10.5	293	1944	7.5 - 8.0
		225/45 R17	91 W	7.5	3.5	51	615	1366	225	8.9	624	25.0	8.3	10.5	293	1934	7.0 - 8.5
		225/50 R17	87 W	7.0	3.5	51	545	1202	219	8.4	626	24.6	8.3	10.5	292	1909	7.0 - 8.0
		225/50 R17	96 V	7.5	3.5	51	710	1565	245	9.6	668	26.3	8.3	10.5	308	2037	6.5 - 8.5
	16"	225/50 R17 RF	98 V	7.0	3.4	50	750	1653	233	9.2	658	25.9	8.5	10.7	304	2007	6.0 - 8.0
		225/50 R17	94 W	7.0	3.5	51	670	1477	233	9.2	658	25.9	8.5	10.7	304	2007	6.0 - 8.0
		215/50 R17	91 W	7.0	3.5	51	615	1366	225	8.9	648	25.5	8.5	10.5	300	1976	6.0 - 7.5
		205/50 R17 RF	93 W	6.5	3.5	51	650	1433	214	8.4	638	25.1	8.2	10.3	296	1946	5.5 - 7.5
		225/55 R17	93 W	7.5	3.5	51	775	1709	245	9.6	690	27.2	8.3	10.5	317	2105	6.5 - 8.5
225/55 R17		97 W	7.0	3.5	51	730	1609	231	9.2	680	26.8	8.3	10.5	313	2074	6.0 - 8.0	
205/45 R16		83 H	7.0	3.5	51	487	1076	206	8.1	590	24.2	8.2	10.3	275	1800	6.5 - 7.5	
205/45 R16		83 V	7.0	3.5	51	487	1076	206	8.1	590	24.2	8.2	10.3	275	1800	6.5 - 7.5	
195/45 R16		80 V	5.5	3.5	51	450	992	195	7.7	532	22.9	8.2	10.3	223	1775	6.0 - 7.5	
225/50 R16		92 W	7.0	3.5	51	630	1389	233	9.2	632	24.9	8.3	10.5	291	1928	6.0 - 8.0	
205/50 R16		87 V	6.5	3.5	51	545	1202	214	8.4	612	24.1	8.2	10.3	283	1867	5.5 - 7.5	
205/50 R16		87 W	6.5	3.5	51	545	1202	214	8.4	612	24.1	8.2	10.3	283	1867	5.5 - 7.5	
195/50 R16		84 V	6.0	3.5	51	500	1102	201	7.9	602	23.7	8.2	10.3	275	1836	5.5 - 7.0	
185/50 R16		81 V	6.0	3.5	51	452	1019	191	7.6	592	23.3	8.2	10.3	275	1806	5.0 - 6.5	
225/55 R16		95 V	7.0	3.5	51	690	1521	233	9.2	654	25.7	8.2	10.5	300	1995	6.0 - 8.0	
225/55 R16		95 W	7.0	3.5	51	690	1521	233	9.2	654	25.7	8.2	10.5	300	1995	6.0 - 8.0	
215/55 R16 RF		97 V	7.0	3.4	50	730	1609	236	9.3	645	25.4	8.3	10.5	296	1967	6.0 - 7.5	
215/55 R16		93 V	7.0	3.5	51	650	1433	226	8.9	645	25.4	8.3	10.5	296	1967	6.0 - 7.5	
205/55 R16	91 V	6.5	3.5	51	615	1366	214	8.4	622	24.9	8.2	10.3	291	1928	5.5 - 7.5		
205/55 R16	91 W	6.5	3.5	51	615	1366	214	8.4	622	24.9	8.2	10.3	291	1928	5.5 - 7.5		
225/60 R16	100 W	7.0	3.5	51	800	1764	240	9.4	688	27.1	8.3	10.5	313	2098	6.5 - 8.5		
225/60 R16	98 W	6.5	3.5	51	750	1653	228	9.0	676	26.6	8.3	10.5	308	2062	6.0 - 8.0		
215/60 R16	95 V	6.5	3.5	51	690	1521	221	8.7	664	26.1	8.8	11.1	304	2025	6.0 - 7.5		
215/60 R16	95 W	6.5	3.5	51	690	1521	221	8.7	664	26.1	8.8	11.1	304	2025	6.0 - 7.5		
205/60 R16	92 H	6.0	3.5	51	630	1389	209	8.2	652	25.7	8.8	11.1	295	1959	5.5 - 7.5		
205/60 R16	92 V	6.0	3.5	51	630	1389	209	8.2	652	25.7	8.8	11.1	295	1959	5.5 - 7.5		
205/65 R16	98 H	8.5	3.5	51	750	1653	221	8.7	686	27.0	8.3	10.5	312	2092	6.0 - 7.5		

* RF : Reinforced

		bar	psi	kg	lbs	mm	inch	mm	inch	mm	mm						
15"	Black Sidewall																
	15"	205/50 R15	86 V	6.5	3.5	51	530	1168	214	8.4	582	23.1	8.2	10.3	271	1790	5.5 - 7.5
		195/50 R15	82 H	6.0	3.5	51	475	1047	201	7.9	577	22.7	8.2	10.3	267	1760	5.5 - 7.0
		195/50 R15	82 V	6.0	3.5	51	475	1047	201	7.9	577	22.7	8.2	10.3	267	1760	5.5 - 7.0
		195/55 R15	85 H	6.0	3.5	51	515	1135	201	7.9	595	23.4	8.2	10.3	274	1815	5.5 - 7.0
		185/55 R15	82 H	6.0	3.5	51	475	1047	194	7.6	585	23.0	8.2	10.3	270	1784	5.0 - 6.5
		175/55 R15	77 T	5.5	3.0	44	412	908	182	7.2	575	22.6	7.1	8.9	265	1748	5.0 - 6.0
	14"	225/60 R15	96 V	5.5	3.5	51	710	1565	228	9.0	651	25.6	8.3	10.5	296	1986	6.0 - 8.0
		215/60 R15	94 V	6.5	3.5	51	690	1521	221	8.7	639	25.2	8.3	10.5	291	1949	6.0 - 7.5
		205/60 R15	91 V	6.0	3.5	51	615	1366	201	7.9	615	24.2	8.2	10.3	282	1876	5.5 - 7.5
		205/60 R15	91 W	6.0	3.5	51	615	1366	209	8.2	627	24.7	8.2	10.3	285	1912	5.5 - 7.5
		195/60 R15	88 V	6.0	3.5	51	560	1235	201	7.6	615	24.2	8.2	10.3	282	1876	5.5 - 7.0
		185/60 R15	84 H	5.5	3.5	51	500	1102	189	7.4	603	23.7	8.2	10.3	277	1839	5.0 - 6.5
		155/60 R15	74 T	4.5	3.0	44	375	827	157	6.2	597	22.3	7.3	9.2	261	1729	4.5 - 5.5
		215/65 R15 RF	100 H	6.5	6.4	91	800	1764	221	8.7	661	26.0	8.3	10.5	300	2016	6.0 - 7.5
		205/65 R15	94 V	6.0	3.5	51	670	1477	209	8.2	647	25.5	8.2	10.3	294	1973	5.5 - 7.5
		205/65 R15	94 W	6.0	3.5	51	670	1477	209	8.2	647	25.5	8.2	10.3	294	1973	5.5 - 7.5
		195/65 R15	91 H	6.0	3.5	51	615	1366	201	7.9	615	24.2	8.2	10.3	290	1937	5.5 - 7.0
		195/65 R15	91 V	6.0	3.5	51	615	1366	201	7.9	615	24.2	8.2	10.3	290	1937	5.5 - 7.0
	215/70 R15 RF	102 T	6.5	3.4	50	850	1874	224	8.8	683	26.9	8.6	10.8	308	2083	5.5 - 7.0	
	185/55 R14	80 H	6.0	3.5	51	490	992	194	7.6	560	22.0	8.2	10.3	258	1708	5.0 - 6.5	
	195/60 R14	86 V	6.0	3.5	51	530	1168	201	7.9	590	23.2	8.2	10.3	269	1800	5.5 - 7.0	
	185/60 R14	82 V	5.5	3.5	51	475	1047	189	7.4	578	22.8	8.2	10.3	265	1763	5.0 - 6.5	

* RF : Reinforced

UTQCS

Series	Speed	Treadwear	Traction	Temperature
-	H, T	340	A	A
-	W	320	AA	A
-	W	280	AA	A