


**OE**

Original equipment manufacturing  
 Erstausr Stungs-Fertigung  
 Equipment d'origine constructeurs  
 Fabricação de equipamentos originais  
 Neumaticos para equipo original



**SOLUS**

**KH15**



Harmony



Handling

	○	⌘	⌚	⊖		⌞		○		⌚		○	⊖	⌘		
				bar	psi	kg	lbs	mm	inch	mm	inch				mm	x/32"
<b>Black Sidewall</b>																
18"	255 / 60 R 18	108 H	7.5	3.0	44	1000	2205	255	10.0	763	30.0	8.8	11.1	348	2327	7.0 - 9.0
17"	235 / 55 R 17	99 V	7.5	3.0	44	775	1709	235	9.3	687	27.0	8.2	10.3	315	2095	6.5 - 8.5
	235 / 55 R 17 RF	103 V	7.5	3.0	44	875	1929	237	9.3	690	27.2	8.2	10.3	317	2105	6.5 - 8.5
	235 / 60 R 17	102 H	7.0	3.4	50	850	1874	228	9.0	720	28.3	9.1	11.5	328	2196	6.5 - 8.5
16"	205 / 45 R 16	83 V	7.0	3.0	44	487	1074	201	7.9	594	23.4	7.8	9.8	276	1812	6.5 - 7.5
	205 / 50 R 16	87 V	6.5	3.0	44	545	1202	199	7.8	615	24.2	8.4	10.6	285	1876	5.5 - 7.5
	205 / 55 R 16	91 H	6.5	3.0	44	615	1356	212	8.3	634	25.0	8.2	10.3	292	1934	5.5 - 7.5
	235 / 60 R 16	100 H	7.0	3.0	44	800	1764	233	9.2	685	27.0	8.2	10.3	312	2089	6.5 - 8.5
	225 / 60 R 16	98 V	6.5	3.0	44	750	1653	225	8.9	675	26.6	8.2	10.3	308	2059	6.0 - 8.0
	215 / 60 R 16	95 V	6.5	3.0	44	690	1521	221	8.7	663	26.1	8.1	10.2	303	2022	6.0 - 7.5
	205 / 60 R 16	92 H	6.0	3.0	44	630	1389	210	8.3	650	25.6	8.5	10.7	298	1983	5.5 - 7.5
	205 / 60 R 16	92 V	6.0	3.0	44	630	1389	209	8.2	652	25.7	8.1	10.2	299	1989	5.5 - 7.5
	215 / 65 R 16	98 H	6.5	3.0	44	750	1653	222	8.7	685	27.0	8.1	10.2	312	2089	6.0 - 7.5
	225 / 70 R 16	102 H	6.5	3.0	44	850	1874	228	9.0	720	28.3	9.1	11.5	326	2196	6.0 - 7.5

\* RF: Reinforced