

| | Rim | Speed | Load Index | Treadwear | Traction | Temperature | Rolling Resistance | | Fuel Economy | | Wet Grip | | Dry Grip | | Noise | |
|-----------------------|--------------------|-------|------------|-----------|----------|-------------|--------------------|-----|--------------|------|----------|------|----------|------|-----------|-----------|
| | | | | | | | bar | psi | kg | lbs | mm | inch | mm | inch | | mm |
| Black Sidewall | | | | | | | | | | | | | | | | |
| 19" | P 225 / 55 R 19 | 99 H | 7.0 | 3.0 | 44 | 775 | 1709 | 233 | 9.2 | 730 | 28.7 | 8.1 | 10.2 | 338 | 2227 | 6.0 - 8.0 |
| | P 225 / 55 R 19 | 99 T | 7.0 | 3.0 | 44 | 775 | 1709 | 233 | 9.2 | 730 | 28.7 | 8.1 | 10.2 | 338 | 2227 | 6.0 - 8.0 |
| 18" | P 245 / 45 R 18 | 96 H | 8.0 | 3.0 | 44 | 710 | 1565 | 255 | 10.0 | 687 | 27.0 | 8.0 | 10.1 | 318 | 2095 | 7.5 - 9.0 |
| | P 235 / 50 R 18 | 97 V | 7.5 | 3.0 | 44 | 730 | 1609 | 242 | 9.5 | 688 | 27.1 | 8.0 | 10.1 | 319 | 2098 | 6.5 - 8.5 |
| | P 225 / 50 R 18 | 94 H | 7.0 | 3.0 | 44 | 670 | 1477 | 233 | 9.2 | 683 | 26.9 | 8.0 | 10.1 | 317 | 2083 | 6.0 - 8.0 |
| | P 255 / 55 R 18 | 104 H | 8.0 | 3.0 | 44 | 900 | 1984 | 265 | 10.4 | 737 | 29.0 | 8.0 | 10.1 | 338 | 2248 | 7.0 - 9.0 |
| | P 235 / 55 R 18 | 99 H | 7.5 | 3.0 | 44 | 775 | 1709 | 245 | 9.6 | 715 | 28.1 | 8.0 | 10.1 | 329 | 2181 | 6.5 - 8.5 |
| | P 225 / 55 R 18 | 97 H | 7.0 | 3.0 | 44 | 730 | 1609 | 233 | 9.2 | 705 | 27.8 | 8.0 | 10.1 | 325 | 2150 | 6.0 - 8.0 |
| 17" | P 225 / 60 R 18 | 99 H | 6.5 | 3.0 | 44 | 775 | 1709 | 228 | 9.0 | 727 | 28.6 | 8.0 | 10.1 | 334 | 2217 | 6.0 - 8.0 |
| | P 215 / 45 R 17 XL | 90 H | 7.0 | 3.0 | 44 | 600 | 1323 | 218 | 8.6 | 626 | 24.6 | 8.3 | 10.5 | 292 | 1909 | 7.0 - 8.5 |
| | P 215 / 45 R 17 XL | 91 V | 7.0 | 3.0 | 44 | 615 | 1356 | 218 | 8.6 | 626 | 24.6 | 8.3 | 10.5 | 292 | 1909 | 7.0 - 8.5 |
| | P 235 / 50 R 17 | 95 H | 7.5 | 3.0 | 44 | 690 | 1521 | 245 | 9.6 | 668 | 26.3 | 8.1 | 10.2 | 308 | 2037 | 6.5 - 8.5 |
| | P 225 / 50 R 17 | 93 H | 7.0 | 3.0 | 44 | 650 | 1433 | 233 | 9.2 | 660 | 26.0 | 8.1 | 10.2 | 305 | 2013 | 6.0 - 8.0 |
| | P 215 / 50 R 17 | 90 V | 7.0 | 3.4 | 50 | 600 | 1323 | 223 | 8.8 | 645 | 25.4 | 8.3 | 10.5 | 299 | 1967 | 6.0 - 7.5 |
| | P 205 / 50 R 17 | 88 H | 6.5 | 3.0 | 44 | 560 | 1235 | 214 | 8.4 | 638 | 25.1 | 8.1 | 10.2 | 296 | 1946 | 5.5 - 7.5 |
| | P 235 / 55 R 17 | 98 V | 7.5 | 3.0 | 44 | 750 | 1653 | 245 | 9.6 | 690 | 27.2 | 8.1 | 10.2 | 317 | 2105 | 6.5 - 8.5 |
| | P 235 / 55 R 17 | 98 H | 7.5 | 3.0 | 44 | 750 | 1653 | 245 | 9.6 | 690 | 27.2 | 8.1 | 10.2 | 317 | 2105 | 6.5 - 8.5 |
| | P 225 / 55 R 17 | 95 H | 7.0 | 3.0 | 44 | 690 | 1521 | 233 | 9.2 | 680 | 26.8 | 8.0 | 10.1 | 313 | 2074 | 6.0 - 8.0 |
| | P 225 / 55 R 17 | 101 V | 7.0 | 3.0 | 44 | 825 | 1819 | 233 | 9.2 | 680 | 26.8 | 8.0 | 10.1 | 313 | 2074 | 6.0 - 8.0 |
| | P 215 / 55 R 17 | 93 V | 7.0 | 3.0 | 44 | 650 | 1433 | 226 | 8.9 | 668 | 26.3 | 8.0 | 10.1 | 308 | 2037 | 6.0 - 7.5 |
| | P 255 / 60 R 17 | 105 H | 7.5 | 3.0 | 44 | 925 | 2039 | 260 | 10.2 | 738 | 29.1 | 8.0 | 10.1 | 335 | 2251 | 7.0 - 9.0 |
| | P 235 / 60 R 17 | 102 T | 7.0 | 3.0 | 44 | 850 | 1874 | 235 | 9.3 | 713 | 28.1 | 8.8 | 11.1 | 326 | 2175 | 6.5 - 8.5 |
| | P 225 / 60 R 17 | 98 H | 6.5 | 3.0 | 44 | 750 | 1653 | 228 | 9.0 | 702 | 27.6 | 8.0 | 10.1 | 321 | 2141 | 6.0 - 8.0 |
| | P 215 / 60 R 17 | 95 H | 6.5 | 3.0 | 44 | 690 | 1521 | 221 | 8.7 | 690 | 27.2 | 8.0 | 10.1 | 317 | 2105 | 6.0 - 7.5 |
| | P 235 / 65 R 17 | 103 H | 7.0 | 3.0 | 44 | 875 | 1929 | 240 | 9.4 | 738 | 29.1 | 8.0 | 10.1 | 335 | 2251 | 6.5 - 8.5 |
| | P 225 / 65 R 17 | 100 H | 6.5 | 3.0 | 44 | 800 | 1764 | 228 | 9.0 | 724 | 28.5 | 8.0 | 10.1 | 330 | 2208 | 6.0 - 8.0 |
| P 215 / 65 R 17 | 98 H | 6.5 | 3.0 | 44 | 750 | 1653 | 221 | 8.7 | 712 | 28.0 | 8.0 | 10.1 | 325 | 2172 | 6.0 - 7.5 | |
| 16" | P 205 / 45 R 16 | 83 V | 7.0 | 3.0 | 44 | 487 | 1074 | 201 | 7.9 | 594 | 23.4 | 7.8 | 9.8 | 276 | 1812 | 6.5 - 7.5 |
| | P 235 / 55 R 16 | 96 H | 7.5 | 3.0 | 44 | 710 | 1565 | 245 | 9.6 | 664 | 26.1 | 8.0 | 10.1 | 304 | 2025 | 6.5 - 8.5 |
| | P 225 / 55 R 16 | 94 H | 7.0 | 3.0 | 44 | 670 | 1477 | 233 | 9.2 | 654 | 25.7 | 8.0 | 10.1 | 300 | 1995 | 6.0 - 8.0 |
| | P 215 / 55 R 16 | 91 H | 7.0 | 3.0 | 44 | 615 | 1356 | 226 | 8.9 | 642 | 25.3 | 8.0 | 10.1 | 295 | 1958 | 6.0 - 7.5 |
| | P 205 / 55 R 16 | 86 H | 6.5 | 3.0 | 44 | 560 | 1235 | 217 | 8.5 | 627 | 24.6 | 8.0 | 10.1 | 291 | 1928 | 6.0 - 7.5 |

| | Rim | Speed | Load Index | Treadwear | Traction | Temperature | Rolling Resistance | | Fuel Economy | | Wet Grip | | Dry Grip | | Noise | |
|-----------------------|-----------------|-------|------------|-----------|----------|-------------|--------------------|-----|--------------|-----|----------|------|----------|------|-------|-----------|
| | | | | | | | bar | psi | kg | lbs | mm | inch | mm | inch | | mm |
| Black Sidewall | | | | | | | | | | | | | | | | |
| 15" | P 195 / 55 R 15 | 84 V | 6.0 | 3.0 | 44 | 500 | 1102 | 207 | 8.1 | 592 | 23.3 | 8.4 | 10.6 | 273 | 1806 | 5.5 - 7.0 |
| | P 175 / 55 R 15 | 77 T | 5.5 | 3.0 | 44 | 412 | 908 | 182 | 7.2 | 573 | 22.6 | 7.1 | 8.9 | 265 | 1748 | 5.0 - 6.0 |
| | P 215 / 60 R 15 | 93 H | 6.5 | 3.0 | 44 | 650 | 1433 | 221 | 8.7 | 639 | 25.2 | 8.0 | 10.1 | 291 | 1949 | 6.0 - 7.5 |
| | P 205 / 60 R 15 | 90 H | 6.0 | 3.0 | 44 | 600 | 1323 | 209 | 8.2 | 627 | 24.7 | 8.0 | 10.1 | 286 | 1912 | 5.5 - 7.5 |
| | P 195 / 60 R 15 | 87 H | 6.0 | 3.0 | 44 | 545 | 1201 | 201 | 7.9 | 615 | 24.2 | 8.0 | 10.1 | 282 | 1876 | 5.5 - 7.0 |
| | P 155 / 60 R 15 | 74 T | 4.5 | 3.0 | 44 | 375 | 827 | 157 | 6.2 | 567 | 22.3 | 7.3 | 9.2 | 263 | 1729 | 4.5 - 5.0 |
| | P 215 / 65 R 15 | 95 H | 6.5 | 3.0 | 44 | 690 | 1521 | 221 | 8.7 | 645 | 25.4 | 8.0 | 10.1 | 293 | 1967 | 6.0 - 7.5 |
| | P 205 / 65 R 15 | 92 H | 6.0 | 3.0 | 44 | 630 | 1389 | 203 | 8.0 | 645 | 25.4 | 8.1 | 10.2 | 293 | 1967 | 5.5 - 7.5 |
| | P 195 / 65 R 15 | 89 H | 6.0 | 3.0 | 44 | 580 | 1279 | 196 | 7.7 | 636 | 25.0 | 8.0 | 10.1 | 290 | 1940 | 5.5 - 7.0 |
| | P 195 / 65 R 15 | 89 T | 6.0 | 3.0 | 44 | 580 | 1279 | 196 | 7.7 | 636 | 25.0 | 8.0 | 10.1 | 290 | 1940 | 5.5 - 7.0 |
| | P 185 / 65 R 15 | 86 H | 5.5 | 3.0 | 44 | 530 | 1168 | 189 | 7.4 | 621 | 24.4 | 8.0 | 10.1 | 284 | 1894 | 5.0 - 6.5 |
| | P 185 / 65 R 15 | 86 T | 5.5 | 3.0 | 44 | 530 | 1168 | 189 | 7.4 | 621 | 24.4 | 8.0 | 10.1 | 284 | 1894 | 5.0 - 6.5 |
| | P 205 / 70 R 15 | 95 H | 6.0 | 3.0 | 44 | 690 | 1521 | 207 | 8.1 | 668 | 26.3 | 8.1 | 10.2 | 302 | 2037 | 5.0 - 7.0 |
| 14" | P 195 / 60 R 14 | 85 H | 6.0 | 3.0 | 44 | 515 | 1135 | 201 | 7.9 | 590 | 23.2 | 8.0 | 10.1 | 269 | 1800 | 5.5 - 7.0 |
| | P 185 / 60 R 14 | 82 H | 5.5 | 3.0 | 44 | 475 | 1047 | 189 | 7.4 | 578 | 22.8 | 8.0 | 10.1 | 265 | 1763 | 5.0 - 6.5 |
| | P 185 / 65 R 14 | 85 H | 5.5 | 3.0 | 44 | 515 | 1135 | 185 | 7.3 | 594 | 23.4 | 7.8 | 9.8 | 271 | 1812 | 5.0 - 6.5 |
| | P 175 / 70 R 14 | 84 T | 5.0 | 3.0 | 44 | 500 | 1102 | 173 | 6.8 | 600 | 23.6 | 8.0 | 10.1 | 273 | 1830 | 4.5 - 6.0 |

UTQGS

| Rim (Inch) | Speed | Treadwear | Traction | Temperature |
|------------|---------|-----------|----------|-------------|
| 19 | H, T | 440 | A | A |
| 18 | V | 440 | A | A |
| 17 | H, T, V | 440 | A | A |
| 16 - 15 | H, T, V | 440 | AA | A |
| 14 | H, T | 440 | AA | A |