

															
			bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"	mm	mm	

Black Sidewall

19"	275 / 30 ZR 19 RF 96 Y	9.5	3.5	51	710	1565	278	10.9	649	25.6	7.0	8.8	306	1979	9.0 - 10.0
	245 / 35 ZR 19 RF 93 Y	8.5	3.5	51	650	1433	248	9.8	655	25.8	7.0	8.8	309	1998	8.0 - 9.5
	235 / 35 ZR 19 RF 91 Y	8.5	3.5	51	615	1356	241	9.5	647	25.5	7.0	8.8	305	1973	8.0 - 9.5
18"	335 / 30 ZR 18 102 Y	12.0	3.5	51	850	1874	343	13.5	659	25.9	6.8	8.6	307	2010	11.5 - 12.5
	295 / 30 ZR 18 94 Y	10.5	3.5	51	670	1477	301	11.9	635	25.0	6.8	8.6	298	1937	10.0 - 11.0
	285 / 30 ZR 18 93 Y	10.0	3.5	51	650	1433	290	11.4	629	24.8	6.8	8.6	296	1918	9.5 - 10.5
	295 / 35 ZR 18 99 Y	10.5	3.5	51	775	1709	301	11.9	663	26.1	7.3	9.2	309	2022	10.0 - 11.5
	275 / 35 ZR 18 95 Y	9.5	3.5	51	690	1521	278	10.9	649	25.6	7.0	8.8	303	1979	9.0 - 11.0
	265 / 35 ZR 18 93 Y	9.5	3.5	51	650	1433	271	10.7	643	25.3	7.3	9.2	301	1961	9.0 - 10.5
	215 / 35 ZR 18 RF 84 Y	7.5	3.5	51	500	1102	218	8.6	607	23.9	7.0	8.8	287	1851	7.0 - 8.5
	275 / 40 ZR 18 99 Y	9.5	3.5	51	775	1709	278	10.9	677	26.7	6.8	8.6	314	2065	9.0 - 11.0
	245 / 40 ZR 18 93 Y	8.5	3.5	51	650	1433	248	9.8	653	25.7	7.3	9.2	305	1992	8.0 - 9.5
	235 / 40 ZR 18 91 Y	8.5	3.5	51	615	1356	241	9.5	645	25.4	7.0	8.8	302	1967	8.0 - 9.5
	225 / 40 ZR 18 88 Y	8.0	3.5	51	560	1235	230	9.1	637	25.1	7.2	9.1	299	1943	7.5 - 9.0
	17"	315 / 35 ZR 17 102 Y	11.0	3.5	51	850	1874	320	12.6	652	25.7	6.8	8.6	302	1989
285 / 40 ZR 17 100 Y		10.0	3.5	51	800	1764	290	11.4	660	26.0	7.0	8.8	305	2013	9.5 - 11.0
275 / 40 ZR 17 98 Y		9.5	3.5	51	750	1653	278	10.9	652	25.7	7.0	8.8	302	1989	9.0 - 11.0
255 / 40 ZR 17 94 Y		9.0	3.5	51	670	1477	260	10.2	636	25.0	7.0	8.8	296	1940	8.5 - 10.0
245 / 40 ZR 17 91 Y		8.5	3.5	51	615	1356	248	9.8	628	24.7	7.0	8.8	292	1915	8.0 - 9.5
215 / 40 ZR 17 RF 87 W		7.5	3.5	51	545	1201	225	8.9	604	23.8	7.0	8.8	283	1842	7.0 - 8.5
205 / 40 ZR 17 RF 84 Y		7.5	3.5	51	500	1102	214	8.4	595	23.4	7.0	8.8	280	1815	7.0 - 8.0
255 / 45 ZR 17 98 Y		8.5	3.5	51	750	1653	255	10.0	662	26.1	7.0	8.8	306	2019	8.0 - 9.5
245 / 45 ZR 17 95 Y		8.0	3.5	51	690	1521	243	9.6	652	25.7	7.0	8.8	302	1989	7.5 - 9.0
235 / 45 ZR 17 94 Y		8.0	3.5	51	670	1477	236	9.3	644	25.4	7.0	8.8	299	1964	7.5 - 9.0
225 / 45 ZR 17 91 Y		7.5	3.5	51	615	1356	225	8.9	634	25.0	7.2	9.1	295	1934	7.0 - 8.5
215 / 45 ZR 17 87 Y		7.0	3.5	51	545	1201	213	8.4	626	24.6	7.0	8.8	292	1909	7.0 - 8.0
16"	225 / 45 ZR 16 89 Y	7.5	3.5	51	580	1279	224	8.8	606	23.9	7.0	8.8	281	1848	7.0 - 8.5
	205 / 45 ZR 16 RF 87 W	7.0	3.5	51	545	1201	206	8.1	590	23.2	7.0	8.8	275	1800	6.5 - 7.5
	225 / 50 ZR 16 92 W	7.0	3.5	51	630	1389	233	9.2	632	24.9	7.0	8.8	291	1928	6.0 - 8.0
	205 / 55 ZR 16 91 W	6.5	3.5	51	615	1356	214	8.4	632	24.9	7.0	8.8	291	1928	5.5 - 7.5
15"	205 / 50 ZR 15 86 W	6.5	3.5	51	530	1168	214	8.4	632	24.9	7.0	8.8	288	1928	5.5 - 7.5
	195 / 50 R 15 82 V	6.0	3.5	51	475	1047	201	7.9	577	22.7	7.0	8.8	267	1760	5.5 - 7.0
14"	185 / 60 R 14 82 V	5.5	3.5	51	475	1047	189	7.4	578	22.8	7.0	8.8	265	1763	5.0 - 6.5

* RF : Reinforced