



										bar		psi		kg		lbs		mm		inch		mm		inch		mm		inch	
										mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
Black Sidewall																													
21"	295 / 25 R 21 RF	96 Y	10.5	3.4	50	710	1565	301	11.9	681	26.8	8.3	10.5	324	2077	10.0 - 11.0													
	255 / 30 R 21 RF	93 Y	9.0	3.4	50	650	1433	260	10.2	687	27.0	8.3	10.5	327	2095	8.5 - 9.5													
20"	345 / 25 R 20	100 Y	12.5	3.5	51	800	1764	355	14.0	680	26.8	8.0	10.1	321	2074	12.0 - 13.0													
	305 / 25 R 20	93 Y	11.0	3.5	51	650	1433	313	12.3	660	26.0	8.3	10.5	313	2013	10.5 - 11.5													
	295 / 25 R 20 RF	95 Y	10.5	3.4	50	690	1521	301	11.9	656	25.8	8.3	10.5	312	2001	10.0 - 11.0													
	275 / 30 R 20 RF	97 Y	9.5	3.5	51	730	1609	278	10.9	674	26.5	8.5	10.7	319	2056	9.0 - 10.0													
	255 / 30 R 20 RF	92 Y	9.0	3.4	50	630	1389	255	10.0	661	26.0	8.3	10.5	314	2016	8.5 - 9.5													
	235 / 30 R 20 RF	88 Y	8.5	3.4	50	560	1235	241	9.5	647	25.5	8.5	10.7	308	1973	8.5													
	275 / 35 R 20	98 Y	9.5	3.5	51	750	1653	278	10.9	700	27.6	8.5	10.7	329	2135	9.0 - 11.0													
	245 / 35 R 20 RF	95 Y	8.5	3.5	51	690	1521	248	9.8	680	26.8	8.5	10.7	321	2074	8.0 - 9.5													
	225 / 35 R 20 RF	90 Y	8.0	3.5	51	600	1323	230	9.1	660	26.0	8.5	10.7	313	2013	7.5 - 9.0													
	245 / 40 R 20	95 Y	8.5	3.5	51	690	1521	248	9.8	704	27.7	8.5	10.7	330	2147	8.0 - 9.5													
19"	315 / 25 R 19	94 Y	11.5	3.5	51	670	1477	325	12.8	641	25.2	8.3	10.5	303	1955	11.0 - 12.0													
	275 / 30 R 19 RF	96 Y	9.5	3.4	50	710	1565	278	10.9	649	25.6	8.5	10.7	306	1979	9.0 - 10.0													
	265 / 30 R 19 RF	93 Y	9.5	3.4	50	650	1433	271	10.7	643	25.3	8.5	10.7	304	1961	9.0 - 10.0													
	275 / 35 R 19 RF	100 Y	9.5	3.5	51	800	1764	278	10.9	675	26.6	8.5	10.7	316	2059	9.0 - 11.0													
	255 / 35 R 19 RF	96 Y	9.0	3.5	51	710	1565	260	10.2	661	26.0	8.5	10.7	311	2016	8.5 - 10.0													
	245 / 35 R 19 RF	93 Y	8.5	3.4	50	650	1433	248	9.8	655	25.8	8.5	10.7	309	1998	8.0 - 9.5													
	235 / 35 R 19 RF	91 Y	8.5	3.4	50	615	1356	241	9.5	647	25.5	8.5	10.7	305	1973	8.0 - 9.5													
	225 / 35 R 19 RF	88 Y	8.0	3.5	51	560	1235	230	9.1	641	25.2	8.5	10.7	303	1955	7.5 - 9.0													
	225 / 35 R 19 RF	88 Y	8.0	3.4	50	560	1235	230	9.1	641	25.2	8.3	10.5	303	1955	7.5 - 9.0													
	215 / 35 R 19 RF	85 Y	7.5	3.5	51	515	1135	218	8.6	633	24.9	8.5	10.7	300	1931	7.0 - 8.5													
	255 / 40 R 19	96 Y	9.0	3.5	51	710	1565	260	10.2	687	27.0	8.5	10.7	321	2095	8.5 - 10.0													
	245 / 40 R 19 RF	98 Y	8.5	3.5	51	750	1653	248	9.8	679	26.7	8.5	10.7	318	2071	8.0 - 9.5													
	18"	285 / 30 R 18	93 Y	10.0	3.5	51	650	1433	290	11.4	629	24.8	8.5	10.7	296	1918	9.5 - 10.5												
275 / 35 R 18		95 Y	9.5	3.5	51	690	1521	278	10.9	649	25.6	8.5	10.7	303	1979	9.0 - 11.0													
265 / 35 R 18		93 Y	9.5	3.5	51	650	1433	271	10.7	643	25.3	8.5	10.7	301	1961	9.0 - 10.5													
255 / 35 R 18 RF		94 Y	9.0	3.4	50	670	1477	260	10.2	635	25.0	8.5	10.7	298	1937	8.5 - 10.0													
245 / 35 R 18		88 Y	8.5	3.5	51	560	1235	248	9.8	629	24.8	8.5	10.7	296	1918	8.0 - 9.5													
225 / 35 R 18 RF		87 Y	8.0	3.4	50	545	1201	230	9.1	615	24.2	8.3	10.5	290	1876	7.5 - 9.0													
255 / 40 R 18		95 Y	9.0	3.5	51	690	1521	260	10.2	661	26.0	8.5	10.7	308	2016	8.5 - 10.0													
245 / 40 R 18 RF		97 Y	8.5	3.4	50	730	1609	248	9.8	653	25.7	8.5	10.7	305	1992	8.0 - 9.5													
235 / 40 R 18		93 Y	8.5	3.5	51	650	1433	241	9.5	645	25.4	8.5	10.7	302	1967	8.0 - 9.5													
255 / 45 R 18 RF		103 Y	8.5	3.4	50	875	1929	255	10.0	687	27.0	8.5	10.7	318	2095	8.0 - 9.5													
245 / 45 R 18 RF		100 Y	8.0	3.4	50	800	1764	243	9.6	677	26.7	8.5	10.7	314	2065	7.5 - 9.0													
17"		245 / 35 R 17	87 Y	8.5	3.5	51	545	1201	248	9.8	604	23.8	8.5	10.7	283	1842	8.0 - 9.5												
	255 / 40 R 17	94 Y	9.0	3.5	51	670	1477	260	10.2	636	25.0	8.5	10.7	296	1940	8.5 - 10.0													
	245 / 40 R 17	91 Y	8.5	3.5	51	615	1356	248	9.8	628	24.7	8.5	10.7	292	1915	8.0 - 9.5													
	235 / 40 R 17 RF	94 Y	8.5	3.4	50	670	1477	241	9.5	620	24.4	8.5	10.7	289	1891	8.0 - 9.5													
	225 / 40 R 17 RF	90 Y	8.0	3.5	51	600	1323	230	9.1	612	24.1	8.5	10.7	286	1867	7.5 - 9.0													
	215 / 40 R 17	83 W	7.5	3.5	51	487	1074	218	8.6	604	23.8	8.5	10.7	283	1842	7.0 - 8.5													
	205 / 40 R 17 RF	84 Y	7.5	3.4	50	500	1102	212	8.3	596	23.5	8.5	10.7	280	1818	7.0 - 8.0													
	235 / 45 R 17	94 Y	8.0	3.5	51	670	1477	236	9.3	644	25.4	8.5	10.7	299	1964	7.5 - 9.0													
	225 / 45 R 17 RF	94 Y	7.5	3.4	50	670	1477	225	8.9	634	25.0	8.5	10.7	295	1934	7.0 - 8.5													
	215 / 45 R 17 RF	91 W	7.0	3.4	50	615	1356	213	8.4	626	24.6	8.5	10.7	292	1909	7.0 - 8.0													

* RF : Reinforced

UTQGS

Series	Speed	Treadwear	Traction	Temperature
25 ~ 45	W, Y	300	AA	A