

		bar	psi	kg	lbs	mm	inch	mm	inch	mm	inch	mm	inch
24"	275/25 R 24	96 W	10.0	3.4	50	710	1545	278	10.9	751	29.6	8.3	10.5
	275/30 R 24 RF	101 W	9.5	3.4	50	875	1893	280	11.1	776	30.6	8.3	10.5
	295/30 R 24 RF	97 W	9.0	3.4	50	720	1609	270	10.6	765	30.0	8.3	10.5
22"	295/25 R 22 RF	97 W	10.5	3.4	50	720	1609	301	11.9	707	27.8	8.3	10.5
	285/25 R 22	102 W	10.5	3.4	50	850	1874	295	11.6	705	27.8	8.3	10.5
	251/30 R 22 XF	95 W	9.0	3.5	51	690	1521	270	10.6	713	28.1	8.3	10.5
20"	245/30 R 22 XF	92 W	8.5	3.5	51	610	1389	258	10.2	707	27.8	8.3	10.5
	245/40 R 20	95 W	8.5	3.5	51	690	1521	258	10.2	704	27.7	8.3	10.5
	245/45 R 20	101 W	8.5	3.5	51	825	1811	243	9.6	728	28.7	8.3	10.5
18"	245/45 R 20	94 W	8.0	3.5	51	775	1709	253	10.0	728	28.7	8.3	10.5
	275/35 R 18	95 W	9.5	3.5	51	690	1521	278	10.9	649	25.6	8.3	10.5
	265/35 R 18	91 W	9.5	3.5	51	650	1433	271	10.7	643	25.3	8.5	10.7
	255/35 R 18	90 W	9.0	3.5	51	600	1323	260	10.2	635	25.0	8.5	10.7
	215/35 R 18 XF	84 W	7.5	3.4	50	520	1102	218	8.5	607	23.9	8.5	10.7
	275/40 R 18	99 W	9.5	3.5	51	775	1709	278	10.9	677	26.7	8.3	10.5
	245/40 R 18	93 W	8.5	3.5	51	650	1433	248	9.8	651	25.7	8.5	10.7
	235/40 R 18 RF	75 W	8.5	3.4	50	690	1521	241	9.5	645	25.4	8.5	10.7
	225/40 R 18 RF	92 W	8.0	3.4	50	630	1389	230	9.1	617	25.1	8.5	10.7
	255/45 R 18	93 W	8.5	3.5	51	775	1709	255	10.0	682	27.0	8.5	10.7
	245/45 R 18 RF	100 W	8.0	3.5	51	800	1764	243	9.6	677	26.7	8.5	10.7
	235/45 R 18	94 W	8.0	3.5	51	670	1477	236	9.3	669	26.3	8.5	10.7
	225/45 R 18 RF	95 W	7.5	3.4	50	690	1521	225	8.9	659	25.9	8.5	10.7
	215/45 R 18 RF	93 W	7.0	3.5	51	650	1433	213	8.4	651	25.6	8.5	10.7
	235/50 R 18	97 W	7.5	3.5	51	730	1609	245	9.6	693	27.3	8.5	10.7
17"	285/40 R 17	100 W	10.0	3.5	51	800	1764	290	11.4	660	26.0	8.3	10.5
	275/40 R 17	98 W	9.5	3.5	51	730	1609	278	10.9	652	25.7	8.3	10.5
	265/40 R 17	94 W	9.0	3.5	51	670	1477	260	10.2	626	25.0	8.5	10.7
	245/40 R 17	91 W	8.5	3.5	51	615	1356	248	9.8	618	24.7	8.5	10.7
	235/40 R 17 RF	94 W	8.5	3.4	50	670	1477	241	9.5	610	24.4	8.5	10.7
	215/40 R 17 RF	87 W	7.5	3.4	50	545	1201	218	8.6	604	23.8	8.5	10.7
	205/40 R 17 RF	84 W	7.5	3.4	50	520	1102	216	8.5	596	23.5	8.5	10.7
	255/45 R 17	98 W	8.5	3.5	51	770	1653	255	10.0	682	26.1	8.5	10.7
	245/45 R 17	95 W	8.0	3.5	51	690	1521	243	9.6	652	25.7	8.5	10.7
	235/45 R 17	94 W	8.0	3.5	51	670	1477	236	9.3	644	25.4	8.5	10.7
	225/45 R 17 RF	94 W	7.5	3.4	50	670	1477	235	8.9	634	25.0	8.5	10.7
	215/45 R 17 RF	91 W	7.0	3.4	50	615	1356	213	8.4	625	24.6	8.5	10.7
	255/50 R 17	101 W	8.0	3.5	51	825	1811	265	10.4	688	27.1	8.5	10.7
	235/50 R 17	93 W	7.5	3.5	51	710	1585	245	9.6	668	26.1	8.5	10.7
	225/50 R 17	94 W	7.0	3.5	51	670	1477	232	9.2	632	24.9	8.5	10.7
215/50 R 17	91 W	7.0	3.5	51	615	1356	224	8.9	648	25.5	8.5	10.7	
205/50 R 17 RF	89 W	6.5	3.4	50	650	1433	216	8.4	618	25.1	8.5	10.7	
235/55 R 17	97 W	7.5	3.5	51	775	1709	245	9.6	689	27.1	8.5	10.7	
225/55 R 17	97 W	7.0	3.5	51	730	1609	231	9.2	654	25.7	8.5	10.7	
215/55 R 17	94 W	7.0	3.5	51	670	1477	236	9.4	668	26.3	8.5	10.7	

* RF: Reinforced

		bar	psi	kg	lbs	mm	inch	mm	inch	mm	inch	mm	inch
16"	205/40 R 16 RF	83 W	7.5	3.4	50	487	1074	212	8.3	570	22.4	8.5	10.7
	205/45 R 16 RF	87 W	7.0	3.4	50	545	1201	206	8.1	590	23.2	8.5	10.7
	245/50 R 16	97 W	7.5	3.5	51	730	1609	253	10.0	682	26.7	8.5	10.7
	225/60 R 16	92 W	7.0	3.5	51	630	1389	231	9.2	632	24.9	8.5	10.7
	215/50 R 16	90 W	7.0	3.5	51	600	1323	225	8.9	622	24.5	8.5	10.7
	205/50 R 16	87 W	6.5	3.5	51	545	1201	214	8.4	611	24.1	8.5	10.7
	195/50 R 16	84 W	6.0	3.5	51	500	1102	201	7.9	602	23.7	8.3	10.5
	225/55 R 16	95 W	7.0	3.5	51	690	1521	233	9.2	654	25.7	8.5	10.7
	215/55 R 16	93 W	7.0	3.5	51	650	1433	226	8.9	642	25.3	8.5	10.7
	205/55 R 16	91 W	6.5	3.5	51	615	1356	214	8.4	630	25.9	8.5	10.7
15"	225/60 R 16	100 V	7.0	3.5	51	800	1764	240	9.4	688	27.1	8.5	10.7
	225/65 R 16	98 V	6.5	3.5	51	750	1653	228	9.0	676	26.6	8.5	10.7
	205/50 R 15	86 W	6.5	3.5	51	530	1168	214	8.4	587	23.1	8.5	10.7
	205/55 R 15	88 V	6.5	3.5	51	560	1235	214	8.4	607	23.9	8.5	10.7
	195/55 R 15	85 V	6.0	3.5	51	515	1135	201	7.9	595	23.4	8.3	10.5
	225/60 R 15	96 V	6.5	3.5	51	710	1565	228	9.0	651	25.4	8.5	10.7
	205/60 R 15	91 W	6.0	3.5	51	615	1356	209	8.2	627	24.7	8.4	10.6
	195/60 R 15	88 V	6.0	3.5	51	560	1235	201	7.9	616	24.2	8.4	10.6
	205/65 R 15	94 V	6.0	3.5	51	670	1477	209	8.2	647	25.5	8.4	10.6
	195/65 R 15	91 V	6.0	3.5	51	615	1356	201	7.9	635	25.0	8.0	10.1

* RF: Reinforced

UTQGS				
Series	Speed	Treadwear	Traction	Temperature
60 I	V	410	A	A
55 I	W	420	AA	A