



				bar	psi	kg	lbs	mm	inch	mm	inch				mm	x/32"
Black Sidewall																
18"	225 / 40 R 18	88 W	8.0	3.5	51	560	1235	230	9.1	637	25.1	8.1	10.2	299	1943	7.5 - 9.0
17"	215 / 40 R 17	83 W	7.5	3.5	51	487	1074	218	8.6	604	23.8	8.1	10.2	283	1842	7.0 - 8.5
	235 / 45 R 17 RF	97 W	8.0	3.4	50	730	1609	236	9.3	644	25.4	8.1	10.2	299	1964	7.5 - 9.0
	225 / 45 R 17	91 W	7.5	3.5	51	615	1356	225	8.9	634	25.0	8.1	10.2	295	1934	7.0 - 8.5
	215 / 45 R 17	87 W	7.0	3.5	51	545	1201	213	8.4	626	24.6	8.1	10.2	292	1909	7.0 - 8.0
	225 / 50 R 17 RF	98 W	7.0	3.4	50	750	1653	231	9.1	656	25.8	8.3	10.5	303	2001	6.0 - 8.0
	215 / 50 R 17	91 V	7.0	3.5	51	615	1356	226	8.9	648	25.5	8.3	10.5	300	1976	6.0 - 7.5
	235 / 55 R 17 RF	103 W	7.5	3.4	50	875	1929	243	9.6	690	27.2	8.3	10.5	317	2105	6.5 - 8.5
	225 / 55 R 17 RF	101 V	7.0	3.4	50	825	1819	231	9.1	680	26.8	8.1	10.2	313	2074	6.0 - 8.0
215 / 55 R 17 RF	98 W	7.0	3.4	50	750	1653	226	8.9	668	26.3	8.3	10.5	308	2057	6.0 - 7.5	
16"	205 / 45 R 16	83 W	7.0	3.5	51	487	1074	206	8.1	590	23.2	8.1	10.2	275	1800	6.5 - 7.5
	205 / 50 R 16	87 V	6.5	3.5	51	545	1201	214	8.4	612	24.1	8.1	10.2	283	1867	5.5 - 7.5
	235 / 55 R 16	97 V	7.5	3.5	51	730	1609	245	9.6	674	26.5	8.3	10.5	308	2056	6.5 - 8.5
	225 / 55 R 16 RF	99 V	7.0	3.5	51	775	1709	233	9.2	654	25.7	8.3	10.5	300	1995	6.0 - 8.0
	215 / 55 R 16	93 V	7.0	3.5	51	650	1433	226	8.9	642	25.3	8.3	10.5	295	1958	6.0 - 7.5
	205 / 55 R 16	91 V	6.5	3.5	51	615	1356	214	8.4	632	24.9	8.3	10.5	291	1928	5.5 - 7.5
	235 / 60 R 16	100 W	7.0	3.5	51	800	1764	236	9.3	686	27.0	8.3	10.5	312	2092	6.5 - 8.5
	225 / 60 R 16	98 V	6.5	3.5	51	750	1653	224	8.8	674	26.5	8.3	10.5	308	2056	6.0 - 8.0
215 / 60 R 16	95 V	6.5	3.5	51	690	1521	217	8.5	662	26.1	8.3	10.5	303	2019	6.0 - 7.5	
205 / 60 R 16 RF	96 V	6.0	3.4	50	710	1565	206	8.1	652	25.7	8.3	10.5	299	1989	5.5 - 7.5	
15"	205 / 50 R 15	86 V	6.5	3.5	51	530	1168	214	8.4	587	23.1	8.1	10.2	271	1790	5.5 - 7.5
	205 / 55 R 15	88 V	6.5	3.5	51	560	1235	214	8.4	607	23.9	8.3	10.5	279	1851	5.5 - 7.5
	195 / 55 R 15	85 V	6.0	3.5	51	515	1135	201	7.9	595	23.4	8.3	10.5	274	1815	5.5 - 7.0
	225 / 60 R 15	96 V	6.5	3.5	51	710	1565	224	8.8	649	25.6	8.3	10.5	295	1980	6.0 - 8.0
	215 / 60 R 15	94 V	6.5	3.5	51	670	1477	221	8.7	639	25.2	8.3	10.5	291	1949	6.0 - 7.5
	205 / 60 R 15	91 V	6.0	3.5	51	615	1356	205	8.1	625	24.6	8.3	10.5	286	1906	5.5 - 7.5
	195 / 60 R 15	88 V	6.0	3.5	51	560	1235	199	7.8	615	24.2	8.3	10.5	282	1876	5.5 - 7.0
	215 / 65 R 15 RF	100 V	6.5	3.4	50	800	1764	221	8.7	661	26.0	8.3	10.5	300	2016	6.0 - 7.5
205 / 65 R 15	94 V	6.0	3.5	51	670	1477	205	8.1	645	25.4	8.3	10.5	293	1967	5.5 - 7.5	
14"	205 / 60 R 14	89 H	6.0	3.5	51	580	1279	209	8.2	600	23.6	8.3	10.5	273	1830	5.5 - 7.5
	205 / 65 R 14	91 V	6.0	3.5	51	615	1356	209	8.2	622	24.5	8.3	10.5	282	1897	5.5 - 7.5



Aroma Tire

Black Sidewall																
17"	235 / 55 R 17 RF	103 W	7.5	3.4	50	875	1929	243	9.6	690	27.2	8.3	10.5	317	2105	6.5 - 8.5
16"	235 / 60 R 16	100 V	7.0	3.5	51	800	1764	236	9.3	686	27.0	8.3	10.5	312	2092	6.5 - 8.5
	225 / 60 R 16	98 V	6.5	3.5	51	750	1653	224	8.8	674	26.5	8.3	10.5	308	2056	6.0 - 8.0
	215 / 60 R 16	95 V	6.5	3.5	51	690	1521	217	8.5	662	26.1	8.3	10.5	303	2019	6.0 - 7.5
	205 / 60 R 16 RF	96 V	6.0	3.4	50	710	1565	206	8.1	652	25.7	8.3	10.5	299	1989	5.5 - 7.5
16"	205 / 65 R 15	94 V	6.0	3.5	51	670	1477	205	8.1	645	25.4	8.3	10.5	293	1967	5.5 - 7.5

* RF: Reinforced

UTQGS

Series	Speed	Treadwear	Traction	Temperature
40 - 65	H, V, W	380	A	A