

												mm		mm		
												bar	psi	kg	lbs	
Black Sidewall																
18"	265/35 R 18 RF	97 V	9.5	3.0	44	690	1521	271	10.7	643	25.3	9.0	11.3	301	1961	9.0 - 10.5
	225/40 R 18 RF	92 V	8.0	3.0	44	630	1389	230	9.1	637	25.1	9.0	11.3	299	1943	7.5 - 9.0
17"	235/45 R 17	94 V	8.0	3.0	44	670	1477	236	9.3	644	25.4	9.0	11.3	299	1964	7.5 - 9.0
	225/45 R 17	91 V	7.5	3.0	44	615	1356	225	8.9	634	25.0	9.0	11.3	295	1934	7.0 - 8.5
	225/50 R 17 RF	98 V	7.0	3.4	50	750	1653	233	9.2	658	25.9	9.0	11.3	304	2007	6.0 - 8.0
	205/50 R 17 RF	93 V	6.5	3.0	44	650	1433	222	8.7	638	25.1	8.8	11.1	296	1946	5.5 - 7.5
	225/55 R 17	97 V	7.0	3.0	44	730	1609	233	9.2	680	26.8	9.0	11.3	313	2074	6.0 - 8.0
	235/55 R 17 RF	103 V	7.5	3.4	50	875	1929	233	9.2	680	26.8	9.0	11.3	313	2074	6.5 - 8.5
16"	225/50 R 16	93 H	7.0	3.0	44	650	1433	233	9.2	632	24.9	9.0	11.3	291	1928	6.0 - 8.0
	205/50 R 16	87 H	6.5	3.0	44	545	1201	214	8.4	612	24.1	9.0	11.3	283	1867	5.5 - 7.5
	225/55 R 16	95 H	7.0	3.0	44	690	1521	233	9.2	654	25.7	9.0	11.3	300	1995	6.0 - 8.0
	215/55 R 16	93 H	7.0	3.0	44	650	1433	226	8.9	642	25.3	9.0	11.3	295	1958	6.0 - 7.5
	215/55 R 16 RF	97 H	7.0	3.4	50	730	1609	224	8.8	646	25.4	8.8	11.1	297	1970	6.0 - 7.5
	205/55 R 16	91 H	6.5	3.0	44	615	1356	214	8.4	632	24.9	9.0	11.3	291	1928	5.5 - 7.5
205/60 R 16 RF	96 H	6.0	3.0	44	710	1565	209	8.2	652	25.7	9.0	11.3	299	1989	5.5 - 7.5	
15"	195/50 R 15	82 H	6.0	3.0	44	475	1047	201	7.9	577	22.7	9.0	11.3	267	1760	5.5 - 7.0
	175/50 R 15	75 H	5.5	3.0	44	387	853	182	7.2	557	21.9	9.0	11.3	259	1699	5.0 - 6.0
	195/55 R 15	85 H	6.0	3.0	44	515	1135	201	7.9	595	23.4	9.0	11.3	274	1815	5.5 - 7.0
	185/55 R 15	82 H	6.0	3.0	44	475	1047	194	7.6	585	23.0	9.0	11.3	270	1784	5.0 - 6.5
	205/60 R 15	91 H	6.0	3.0	44	615	1356	209	8.2	627	24.7	9.0	11.3	286	1912	5.5 - 7.5
	195/60 R 15	88 H	6.0	3.0	44	560	1235	201	7.9	615	24.2	9.2	11.6	282	1876	5.5 - 7.0
	185/60 R 15	84 T	5.5	3.0	44	500	1102	189	7.4	603	23.7	9.0	11.3	277	1839	5.0 - 6.5
	215/65 R 15	96 H	6.5	3.0	44	710	1565	221	8.7	661	26.0	9.0	11.3	300	2016	6.0 - 7.5
	205/65 R 15	94 H	6.0	3.0	44	670	1477	201	7.9	635	25.0	9.0	11.3	290	1937	5.5 - 7.5
	195/65 R 15	91 T	6.0	3.0	44	615	1356	201	7.9	610	24.0	9.2	11.6	280	1861	5.5 - 7.0
	195/65 R 15	91 H	6.0	3.0	44	615	1356	201	7.9	610	24.0	9.2	11.6	280	1861	5.5 - 7.0
	195/65 R 15 RF	95 T	6.0	3.0	44	690	1521	201	7.9	635	25.0	9.2	11.6	290	1937	5.5 - 7.0
	185/65 R 15	88 T	5.5	3.0	44	560	1235	189	7.4	621	24.4	9.2	11.6	284	1894	5.0 - 6.5
	14"	195/60 R 14	86 T	6.0	3.0	44	530	1168	201	7.9	590	23.2	9.2	11.6	269	1800
185/60 R 14		82 T	5.5	3.0	44	475	1047	189	7.4	578	22.8	9.2	11.6	265	1763	5.0 - 6.5
195/65 R 14		90 T	6.0	3.0	44	600	1323	189	7.4	621	24.4	9.2	11.6	281	1894	5.5 - 7.0
185/65 R 14		86 T	5.5	3.0	44	530	1168	189	7.4	596	23.5	9.2	11.6	272	1818	5.0 - 6.5
175/65 R 14		82 T	5.0	3.0	44	475	1047	177	7.0	584	23.0	9.0	11.3	267	1781	5.0 - 6.0
165/65 R 14		79 T	5.0	3.0	44	437	963	170	6.7	570	22.4	9.0	11.3	261	1739	4.5 - 6.0
13"	175/65 R 13	80 T	5.0	3.0	44	450	992	177	7.0	558	22.0	9.0	11.3	254	1702	5.0 - 6.0
	165/65 R 13	77 Q	5.0	3.0	44	412	908	170	6.7	544	21.4	9.0	11.3	248	1659	4.5 - 6.0

* RF: Reinforced



Run-flat Tire

Black Sidewall																
18"	245/40 R 18	93 H	8.5	3.5	51	650	1433	248	9.8	635	25.0	8.8	11.1	298	1937	8.0 9.5
17"	225/45 R 17	91 H	7.5	3.5	51	615	1356	225	8.9	635	25.0	8.8	11.1	295	1937	7.0 8.5
	205/45 R 17	84 H	7.0	3.5	51	500	1102	206	8.1	614	24.2	8.8	11.1	287	1873	6.5 7.5
	225/50 R 17	94 H	7.0	3.5	51	670	1477	233	9.2	658	25.9	8.8	11.1	304	2007	6.0 8.0
16"	205/55 R 16	91 H	6.5	3.5	51	615	1356	214	8.4	632	24.9	9.0	11.3	291	1928	5.5 7.5
	195/55 R 16	87 H	6.0	3.5	51	545	1201	231	9.1	659	25.9	8.8	11.1	302	2010	5.5 7.0