



			bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				mm
<b>Black Sidewall</b>																
15"	195 / 60 R 15	88 H	6.0	3.0	44	560	1235	201	7.9	615	24.2	9.5	12.0	282	1876	5.5 - 7.0
	195 / 65 R 15	91 H	6.0	3.0	44	615	1356	201	7.9	635	25.0	9.0	11.3	290	1937	5.5 - 7.0
	185 / 65 R 15	88 T	5.5	3.0	44	560	1235	189	7.4	621	24.4	9.3	11.7	284	1894	5.0 - 6.5
	195 / 70 R 15 RF	97 S	6.0	3.0	44	730	1609	201	7.9	655	25.8	9.5	12.0	297	1998	5.0 - 6.5
14"	195 / 60 R 14	86 T	6.0	3.0	44	530	1168	202	8.0	590	23.2	9.3	11.7	269	1800	5.5 - 7.0
	185 / 60 R 14	82 T	5.5	2.5	36	510	1124	189	7.4	578	22.8	9.3	11.7	265	1763	5.0 - 6.5
	185 / 65 R 14	86 T	5.5	3.0	44	530	1168	189	7.4	596	23.5	9.3	11.7	272	1818	5.0 - 6.5
	175 / 65 R 14	82 T	5.0	3.0	44	475	1047	177	7.0	584	23.0	8.8	11.1	267	1781	5.0 - 6.0
	185 / 70 R 14	88 T	5.5	3.0	44	560	1235	189	7.4	616	24.3	9.5	12.0	279	1879	4.5 - 6.0
	175 / 70 R 14	84 T	5.0	3.0	44	500	1102	177	7.0	602	23.7	9.0	11.3	274	1836	4.5 - 6.0
	165 / 70 R 14	81 Q	5.0	3.0	44	462	1019	170	6.7	588	23.1	8.5	10.7	268	1793	4.0 - 5.5
	175 / 80 R 14	88 Q	5.0	3.0	44	560	1235	177	7.0	636	25.0	9.0	11.3	287	1940	4.5 - 6.0
13"	155 / 65 R 13	73 Q	4.5	3.0	44	365	805	157	6.2	532	20.9	8.3	10.5	244	1623	4.5 - 5.5
	175 / 70 R 13	82 T	5.0	3.0	44	475	1047	177	7.0	576	22.7	9.0	11.3	261	1757	4.5 - 6.0
	165 / 70 R 13	79 T	5.0	3.0	44	437	963	170	6.7	562	22.1	8.5	10.7	256	1714	4.0 - 5.5
	165 / 70 R 13 RF	83 Q	5.0	3.0	44	487	1074	170	6.7	562	22.1	8.5	10.7	256	1714	4.0 - 5.5
	155 / 70 R 13	75 T	4.5	3.0	44	387	853	157	6.2	548	21.6	8.5	10.7	250	1671	4.0 - 5.0
	145 / 70 R 13	71 Q	4.5	3.0	44	345	761	150	5.9	534	21.0	8.5	10.7	245	1629	3.5 - 5.0
	165 / 80 R 13	83 Q	4.5	3.0	44	487	1074	165	6.5	594	23.4	9.0	11.3	268	1812	4.0 - 5.5
	155 / 80 R 13	79 Q	4.5	3.0	44	437	963	157	6.2	578	22.8	9.0	11.3	262	1763	4.0 - 5.0
	145 / 80 R 13	75 Q	4.0	3.0	44	387	853	145	5.7	562	22.1	8.5	10.7	256	1714	3.5 - 5.0
	135 / 80 R 13	70 Q	3.5	3.0	44	335	739	133	5.2	546	21.5	8.5	10.7	249	1665	3.5 - 4.5

\* RF : Reinforced